KammBar Black Technical Datasheet





The premium aluminium roof bar system for commercial vehicles.

The new generation of commercial vehicles needs the new generation of van accessories. Aerodynamic, stylish and corrosion resistant, KammBar Black is the leading roof bar of choice for professional van users.

Made from anodised aluminium, KammBar Black increases the storage capability of any van, while its modern design not only provides great aesthetics but also limits wind noise. With two pairs of load stops supplied as standard, KammBar Black is the ultimate roof bar system to take your van to the next level.



#KammGeneration

DIMENSIONS				
- Length	(L1)	1240mm - 1420mm - 1600mm - 1700mm		
Leg widthCross tube width	(W1) (W2)	133mm 60mm		
- Leg height - to top of the bar	(H1)	109mm		
Leg height- to bottom of the barLoad stop height	(H2) (H3)	71.5mm 102mm		

WEIGHT			
Bar length	Bar	Combined weight of two legs	Total weight
- 1240mm	1.60 kg	0.76 kg	2.36 kg
- 1420mm	1.83 kg	0.76 kg	2.59 kg
- 1600mm	2.06 kg	0.76 kg	2.82 kg
- 1700mm	2.19 kg	0.76 kg	2.95 kg



KammBar Black Technical Datasheet



Manufactured from anodised aluminium to prevent rusting, making the system extremely durable in all weather conditions.



The unique shape of the bar profile is inspired by the work of Professor Wunibald Kamm - a pioneering aerodynamicist who established that a teardrop shape such as this is ideal for reducing drag.



The strong steel legs are covered by aesthetic composite covers to add to the modern, premium look of the product.



The KammBar Black's aerodynamic shape almost entirely eliminates wind noise.




Supplied with the saddles loosely fastened into place within the legs, allowing for quick and easy fitment.



KammBar Black has been rigorously tested by our inhouse team of design engineers to ensure it is strong and robust enough to withstand the challenges of day-to-day usage.





This bracket is a beacon support that securely holds single & triple bolt fixing beacons in place, increasing the functionality of the system. Sold separately.




Lock kits can be purchased separately to provide additional theft deterrence and security.



Available in two, three and four bar configurations, the KammBar Black comes complete with a fitting kit that includes bespoke pads and spacers, tailored to the mounting points of every vehicle.



All KammBar Black systems are supplied in a single package. This ensures quick and efficient shipping, minimising any risk of delays as opposed to sending multiple packages.



The final touch to our premium roof bar solution, all KammBar Black systems come with two pairs of load stops as standard.

KammBar Black Technical Datasheet



MATERIAL	WHERE USED	ADVANTAGES
Aluminium alloy		
- 6063A T6 - Black powder-coated	- Cross tubes	 Extremely durable, high tensile, yield strength Excellent weight to strength ratio Scratch resistant Great for intricate extrusions with a good surface finish and high corrosion resistance
Composite		
LDPEPolypropylene (PPCP)	Crosstube end capLeg cowl	
Mild steel		
- Mild steel HR4, powdercoat textured black	- Bar leg - Bar saddle	High strengthCorrosion protected1000h salt spray tested
Eivinge		

Fixings


- Multi-grip pop rivets (main connection method)
- Bolts & (self locking) nuts size M8, combination of stainless and galvanised steel

Tools required for installation 🗡

- 10mm and 13mm spanner required, allen key (included)

KammRoller[®]

The KammRoller is now more durable and easier to install than ever. Our design team has successfully reduced its weight without compromising on its strength. Design enhancement includes a transition to boxed profile side arms, increasing rigidity and minimising flex. Its lightweight aluminum construction integrates perfectly with both the KammBar Pro and KammBar Fleet, as well as with modern commercial vehicles. The KammRoller features black powder-coated side arms, paired with a sleek silver roller.



FEATURES

- Made from aluminium and considerably lighter
- Stylish black anodised aluminium
- Quick and easy installation
- Steel roller inserts for a more durable design
- 50kg rated
- Rhino branded end caps
- Bespoke fitment for every vehicle



TECHNICAL

Roller length (RL) 656mm – 816mm – 956mm – 1056mm – 1114mm

Total length (TL)

804mm - 964mm - 1104mm -1204mm - 1262mm Support arm length (SL)

225mm - 300mm - 350mm -430mm - 490mm - 530mm Weight

min 1.28kg / max 2.23kg



